

# SEEMATZ

## Elektromotorische Fernsteuerungen

SEEMATZ elektromotorische Fernsteuerungen sind aus seewasserbeständigem Aluminium gefertigt. Alle Anlagen sind für den professionellen Einsatz geeignet. Alle Fernsteuerungen haben einen Schwenkbereich von  $+165^{\circ}/-165^{\circ}$  horizontal und  $\pm 30^{\circ}$  vertikal, außer das Modell EFNH, welches für die Überkopfmontage mit  $+10^{\circ}/-90^{\circ}$  vertikal ausgestattet ist. Desweiteren haben alle Anlagen Seitenklappen für eine einfache Installation und Wartung.

SEEMATZ electrical remote controls are made of seawater resistant aluminium. All systems are made for professional use. All units have a swivelling range of  $+165^{\circ}/-165^{\circ}$  horizontal and  $\pm 30^{\circ}$  vertical except the model EFNH which is designed for overhungmounting with a vertical swivelling range of  $+10^{\circ}/-90^{\circ}$ . Also all units have sidecovers for easy installation and maintenance.



Technische Details / Technical Features :

	EFA	EFD	EFS	EFN	EFNH
Eingangsspannung Input Power	24 VDC	24 VDC	230 VAC	230 VAC	230 VAC
Heizung Heating	–	-	400 Watt	400 Watt	400 Watt
Halogenleuchtmittel Halogen lamps	bis / up to 2000 Watt	bis / up to 2000 Watt	bis / up to 2000 Watt	bis / up to 2000 Watt	bis / up to 2000 Watt
Xenon/HMI/HBO	-	-	bis / up to 450 Watt	bis / up to 2000 Watt	bis / up to 2000 Watt
LED	bis / up to 150 Watt	bis / up to 150 Watt	bis / up to 150 Watt	bis / up to 150 Watt	bis / up to 150 Watt
Pedestal	Optional	Optional	Optional	Optional	Optional
Elektr. Fokus electrical Focal	-	-	Optional	Optional	optional
bis zu 4 Pulte up to 4 Panels	-	Optional	Optional	Optional	Optional
0° Rückstellung 0° Reset function	-	-	Optional	Optional	Optional
dig. Winkelanzeige digital angle control	-	-	Optional	Optional	Optional

Options:

- Schwenkbereich horizontal 390° / swivelling range up to 390° horizontal

